

AirTV-V1-COB

All Flip-chip COB

- Higher Stability and Reliability
- Super Wider Color Gamut
- Higher Contrast Ratio
- Excellent Thermal Management
- Higher Brightness
- Wider View angle without Color Shift
- Lower Heat Generation



Anti-stress and anti-collision, high stability, real world tested

- › COB + Ebony technology, double protection, double secure.
- › Moisture-proof and dust-proof, anti-corrosion and anti-static.
- › longer lifetime, virtually maintenance free.



No space display, UHD display Stunning visual experience

- › Wider view angle, 170° horizontally and vertically.
- › Pixel-by-pixel calibration technology guarantee higher color fidelity and uniformity.



Energy efficient Efficient heat dissipation

- › Heat conductive cabinet.
- › Panel to cabinet heat dissipation fanless design.
- › Power consumption is reduced by 20% under the same brightness condition.



Unlimited possibilities Unlimited vision

- › Easily configured into 1080P/2K/ 4K/ 8K resolution without size limitations.



HD

AirTV-V1-COB / Specifications

	AirTV-V1-COB 0.8	AirTV-V1-COB 1.2
Physical Pitch	0.8mm	1.2 mm
Pixel Configuration	Flip-chip RGB LED (COB)	Flip-chip RGB LED (COB)
Pixel Density	1,440,000 pixels/m ² 259,200 pixels/panel	640,000 pixels/m ² 115,200 pixels/panel
LED Module Dimensions (mm)	200 × 150	200 × 150
Panel Dimensions (W × H × D) (mm)	400 × 450 × 49	400 × 450 × 49
No. of Modules Per Panel (W × H)	2 × 3	2 × 3
Physical Resolution of Module (W × H)	240 × 180	160 × 120
Physical Resolution of Panel (W × H)	480 × 540	320 × 360
Weight Per Panel	6.2 kg/panel	6.2 kg/panel
Processing	16 bit	16 bit
Colours	281 trillion	281 trillion
Contrast Ratio	20,000 : 1	20,000 : 1
Average Power Consumption	38 - 63 w/panel	38 - 63 w/panel
Max Power Consumption	126 w/panel	126 w/panel
Operating Temp/Humidity	-10 - 40 C / 10% - 60%	-10 - 40 C / 10% - 60%
Storage Temp/Humidity	-30 - 60 C / 10% - 60%	-30 - 60 C / 10% - 60%
Brightness	1000 - 1200 nits	1000 - 1200 nits
Refresh Rate	1,920 - 3,840 Hz	1,920 - 3,840 Hz
Horizontal Viewing Angle	170°	170°
Vertical Viewing Angle	170°	170°
Expected LED Lifetime (Max)	100,000 Hrs	100,000 Hrs
Max Stacking	12 panels	12 panels
Servicing	Front	Front
IP Rating	IP65/IP30	IP65/IP30
Certification	CE*, EMC* ,ClassA*, ETL*, RoHS*	CE*, EMC* ,ClassA*, ETL*, RoHS*

* The products listed above are currently under development

*The specification will be different based on different configuration.

Remark: Just for reference. If any request, welcome to contact us. The final interpretation belongs to ShenZhen CreateLED Electronics Co., Ltd.

Typical Applications

- › Command room
- › Teleconferencing
- › Smart education
- › Security
- › TV studio
- › Medical
- › Smart City
- › Stadium